

CUSTOMER DRAWING NO.

REMARKS

Lubrication : Harmonic Drive Harmonic Grease SK-1A

Cross Roller Bearing Harmonic Grease 4B No.2

Designing and/or Handling of Harmonic Drive Gears (Harmonic Actuators) has to comply with technical information shown in Harmonic Drive Catalog

Rated Torque at 2000r/min	Limit for Repeated Peak Torque	Limit for Average Torque	Limit for Momentary Peak Torque
28 N·m	57 N·m	34 N·m	95 N·m

PROPRIETORSHIP
This drawing (document) is the **PROPERTY** of Harmonic Drive Systems,Inc. and shall not be traced, otherwise copied or used for purposes other than agreed upon, nor communicated to any third party without written permission of Harmonic Drive Systems,Inc.

訂正 REV		承認 DESCRIPTION		日付
A		Correction of misdescription		

仕様 SPEC

尺度 SCALE 1:1

機械加工	0 / 0.5	0.5 / 6	6 / 30	30 / 120	120 / 315	315 / 1000	1000 / 2000
鋳造	±0.05	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2

備考 REMARKS : 特記無き角はC0.2以下、すみのRはR0.4以下

特記号表面アラサ SURFACES MARKED EXCEPT AS NOTED ▽→3.2S ▽▽→1.6S ▽▽▽→0.8S

DWG SIZE A3 | UNIT mm | THIRD ANG

設計 DESIGN	S.Matsse	Oct-29-'12	タイトル TITLE ASSEMBLY DRAWING
検図 VRFD	H.Tukahara	Oct-29-'12	製品名 MTELE SHD-20-100-2UH-LW
承認 APPD	T.Yanagishi	Oct-29-'12	

HARMONIC DRIVE SYSTEMS | TOKYO JAPAN

図番 DWG No C2A4347 — A

本図は（株）ハーモニック・ドライブ・システムズの所有に係わるものです。許可なく（第3者に見せたり、トレースその他の複写及び指定された用途以外には使用しないで下さい。