



REMARKS

Lubrication : Harmonic Drive Harmonic Grease SK-1A
 Cross Roller Bearing Harmonic Grease 4B No.2
 Designing and/or Handling of Harmonic Drive Gears (Harmonic Actuators)
 has to comply with technical information shown in Harmonic Drive Catalog.

CUSTOMER DRAWING NO.

PROPRIETORSHIP
 This drawing (document) is the **PROPERTY** of Harmonic Drive Systems, Inc. and shall not be traced, otherwise copied or used for purposes other than agreed upon, nor communicated to any third party without written permission of Harmonic Drive Systems, Inc.

Rated Torque at 2000r/min	Limit for Repeated Peak Torque	Limit for Average Torque	Limit for Momentary Peak Torque
87 N·m	204 N·m	140 N·m	369 N·m

訂正 REV	来歴 DESCRIPTION	設計 DESIGN	S.Momose	Oct-23-'12	タイトル TITLE	ASSEMBLY DRAWING
仕様 SPEC		検図 VRFD	H.Tukahara	Oct-23-'12	製品名 ARTICLE	SHG-25-100-2UH-LW
機械加工無記号公差 GENERAL TOLERANCE	備考 REMARKS : 特記無き角はC0.2以下、すみの丸みはR0.4以下 無記号表面アラス SURFACES MARKED EXCEPT AS NOTED	承認 APPD	T.Yamagishi	Oct-23-'12	図番 DWG No	C2A4438 -
0 0.5 6 30 120 315 1000	±0.05 ±0.1 ±0.2 ±0.3 ±0.5 ±0.8 ±1.2	50S 25S 6.3S	尺度 SCALE	1:1		
			DWG SIZE	A3	UNIT	mm
			THIRD ANG	☉		
本図は(株)ハーモニック・ドライブ・システムズの所有に係わるものです。許可なく第三者に見せたり、トレースその他の複写及び指定された用途以外には使用しないで下さい。						